

Product Information

ISO Class 5 - 8

Cleanroom Class 100 -100,000 EU Grade B/C/D

SatPax® Polx® Nonwoven

Pre-wetted 100% Polyester Nonwoven Cleanroom Wiper

SatPax® Polx® Nonwoven is a 100% polyester hydroentangled nonwoven wiper recommended for ISO Class 5 and above environments. It is an extremely soft and pliable wiper ideal for all types of sensitive surfaces and an excellent choice for wrapping delicate parts for protection. This pre-wetted format provides a cost-effective and easy-to-use solution versus traditional bulk handling of solvents, maintenance of squirt bottles and inconsistent wetting and cleaning associated with wetting a dry wiper. Additionally, it's critically low fiber and particle generation and minimal non-volatile residues make SatPax® Polx® nonwoven an exceptional choice for streak-free cleaning.



Key Attributes

- 100% polyester hydroentangled nonwoven
- No cellulose components, 100% synthetic
- · Low fiber and particle generation
- Extremely soft and nonabrasive
- · Pre-wetted with consistent IPA / DI Water concentrations and saturation levels
- · Re-sealable solvent resistant packaging with wipers in a c-folded configuration for single withdrawal

Benefits

- · Exceptional cleanliness
- Prevents abrasion with its extremely soft and pliable surface
- Increases cleaning protocol consistency
- · Lot to lot traceability
- Reduces alcohol usage and preparation / handling costs
- Increases cleaning efficiency

Other Class 5 and above Pre-wetted wipers

- SatPax® 1000
- SatPax® 670-R
- SatPax® 550

Applications

- Designed for use in ISO Class 5 and higher cleanroom environments
- Gentle enough for wiping and polishing soft metal and glass surfaces
- Cleaning of optics and other sensitive surfaces
- Cleaning and absorbing oil and grease

Alcohol Mixtures

Alcohol / DI Water mixtures can be varied to fit the customer requirements. Typical mixtures are 70/30 and 9/91 IPA/DI Water.

Saturation Levels

The amount of solution contained in each wiper can be varied according to customer requirements. Higher saturation levels apply more solution to the surface during cleaning.

Sterile Validated Option

For aseptic processing areas, the same wiper material can be provided in a gamma irradiated validated sterile to a 10⁻⁶ sterility assurance level.

www.berkshire.com

Contact: Tel 1 800 242 7000 / 1 413 528 2602 info@berkshire.com

America	Tel 1 413 528 2602	info@berkshire.com
Europe	Tel + 44 1953 562800	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	enquiries@berkshire.com.sg
Japan	Tel 81 3 4530 9883	master@berkshire.co.jp



Technical Data:

Attribute		Units	Value	Test Method
Basis Weight		g/m²	55.7	TAPPI T-410
Caliper		μm	251	TAPPI T-411
Fibers	≥100µm	fibers/cm ²	7.4	IEST-RP-CC004.4, Sec 7.1.3 / Sec 7.2.2 modified
Particles	≥0.5µm	x10 ³ /cm ²	0.34	IEST-RP-CC004.4, Sec 7.1.3 / Sec 7.2.1 modified
Sorbency	Capacity	mL/m²	261	IEST-RP-CC004.4, Sec 9.1 modified / Sec 9.2 modified
	Efficiency	mL/g	4.7	
	Rate	seconds	2	
Non-Volatile Residue	DI Water	g/m²	0.0020	IEST-RP-CC004.4, Sec 8.1.2
	IPA	g/m²	0.0028	
Ions	Na ⁺	ppm	8.9	IEST-RP-CC004.4, Sec 8.2.2
	K ⁺	ppm	1.2	
	Ca ⁺⁺	ppm	21	
	Mg ⁺⁺	ppm	5.0	
	CI-	ppm	11	

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request
- Sorbency capacity, efficiency, and rate performed with 70% IPA

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	IPA/DI	Saturation	VOC % by Weight	Style
SatPax® Polx NW	SPXPNW00112	9x9"(23x23cm)	75	12	70/30	60%	42.0%	C-Fold

Other Berkshire products



Wipers



G

Glove Liners





Documentation Systems



Face Masks



Swabs