

# Durx<sup>®</sup> 670 AS (Aerospace)

55% Cellulose / 45% Polyester Nonwoven Cleanroom Wiper

Durx<sup>®</sup> 670 AS for Aerospace (AS) is a hydroentangled nonwoven blend of 55% cellulose and 45% polyester with no binders or other chemical additives and meets the AMS 3819D, Class 2, Grade A, Form 1 requirements. This combination of properties provides Durx<sup>®</sup> 670 AS with the absorbency level, abrasion resistance, and chemical compatibility required for controlled environments and applications where both cleanliness and economy are critical. Durx<sup>®</sup> 670 AS offers application versatility to meet the specific challenges faced in aerospace processes and applications.

1.12.511				141 (41)			
	ann n						
	114 19 19						
NY 15 4 4		SASAD					말감험
X112415							1201
CEL SUS							
		DATE:					
							831
							14.14
	620493		an tag				
							584 J
RI POLO					111210		1981
							1.31
NI IS NI		de la Cari					
SING			RANK		11.29.22		
						No. The	
			化学生学生	REAL ST		1913 181	

### Other AS (Aerospace) products

- SatPax<sup>®</sup> 670 AS
- Microseal SuperSorb<sup>®</sup> AS

#### **Key Attributes**

- 55% cellulose / 45% polyester hydroentangled nonwoven blend
- No binders or other chemical additives

#### Benefits

- Meets AMS 3819D requirements, Class 2, Grade A, Form 1
- Meets BMS 15-5 requirements
- Excellent combination of the synthetic polyester strength and cleanliness with the absorbent characteristics of cellulose
- Smooth, highly absorbent and durable
- Low extractable levels and particle counts
- Chemically compatible with common cleaning solutions
- Economical

### Applications

- Designed for use in ISO Class 5 and higher cleanroom environments
- General equipment wrap and wipe downs
- General purpose wiping applications
- Ideal for use on flyaway components
- Paint preparation
- · Wiping and cleaning of sensitive optics, such as sensors and glass
- Microelectronics and ESD
- General maintenance cleaning, such as oil and adhesive

## **Pre-Wetted Option**

The same wiper material can be provided in pre-wetted formats for reduced VOC emissions, increased convenience, increased productivity, improved solvent control and cleaning protocol repeatability and reduced costs.

## www.berkshire.com

Contact: Tel 1 800 242 7000 / 1 413 528 2602 info@berkshire.com

America	Tel 1 413 528 2602	info@berkshire.com
Europe	Tel + 44 1953 562800	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	enquiries@berkshire.com.sg
Japan	Tel 81 3 4530 9883	master@berkshire.co.jp



#### **Technical Data**

Attribute		Units	Value	Test Method
Basis Weight		g/m <sup>2</sup>	68.0	TAPPI T-410
Caliper		μm	264	TAPPI T-411
Fibers	≥100µm	fibers/cm <sup>2</sup>	160	IEST-RP-CC004.4 Sec 7.1.3/Sec 7.2.2 modified
Particles	<u>≥</u> 0.5µm	x10 <sup>3</sup> /cm <sup>2</sup>	10	IEST-RP-CC004.4 Sec 7.1.3/Sec 7.2.1 modified
Sorbency	Capacity	mL/m²	320	IEST-RP-CC004.4 Sec 9.1 / Sec 9.2 modified
	Efficiency	mL/g	4.7	
	Rate	seconds	2	
Non-Volatile Residue	DI Water	g/m²	0.028	IEST-RP-CC004.4 Sec 8.1.2
	IPA	g/m²	0.0038	
Ions	Na⁺	ppm	62	IEST-RP-CC004.4 Sec 8.2.2
	K+	ppm	5.9	
	Ca++	ppm	22	
	Mg <sup>++</sup>	ppm	5.0	
	CI	ppm	31	

Notes

•

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
  - Third party testing can be performed upon request

### **Order Information**

Product	Number	Size	Shts/pk	Pks/cs	Style
Durx <sup>®</sup> 670 AS	DR670090920AS	9x9" (23x23cm)	300	20	Stacked
Durx <sup>®</sup> 670 AS	DR670121220AS	12x12" (30x30cm)	150	20	Stacked



# www.berkshire.com

Contact: Tel 1 800 242 7000 / 1 413 528 2602 / info@berkshire.com